



# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Product form : Mixture  
Trade name : TECH-FLEX Black Primer 1L  
Type of product : Adhesives  
Product group : Trade product

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

##### 1.2.1. Relevant identified uses

Intended for general public

##### 1.2.2. Uses advised against

No additional information available

#### 1.3. Details of the supplier of the safety data sheet

INTERKIM

Tel: 216 577 22 34 (2 hat)

Fax: 216 577 22 36

E-mail: [info@interkim.net](mailto:info@interkim.net)

İnönü Mah. Alpkaya Cad. Kestel Apt.

No: 58/5

ATAŞEHİR/İSTANBUL

#### 1.4. Emergency telephone number

Emergency number : 112

Country	Organisation/Company	Address	Emergency number	Comment
United Kingdom	National Poisons Information Service (Newcastle Centre) Regional Drugs and Therapeutics Centre	Claremont Place Newcastle-upon-Tyne NE1 4LP Newcastle	0844 892 0111 (UK only, Monday to Friday, 08.00 to 18.00 hours)	

### SECTION 2: Hazards identification

#### 2.1. Classification of the substance or mixture

##### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Flammable liquids, Category 2	H225	
Skin corrosion/irritation, Category 2	H315	Calculation method
Serious eye damage/eye irritation, Category 2	H319	Calculation method
Sensitisation — Respiratory, Category 1	H334	Calculation method
Sensitisation — Skin, Category 1	H317	Calculation method
Carcinogenicity, Category 2	H351	Calculation method
Specific target organ toxicity — Single exposure, Category 3, Narcosis	H336	Calculation method
Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation	H335	Calculation method
Hazardous to the aquatic environment — Chronic Hazard, Category 3	H412	

Full text of hazard classes and H-statements : see section 16

##### Adverse physicochemical, human health and environmental effects

Highly flammable liquid and vapour. Suspected of causing cancer. May cause drowsiness or dizziness. May cause respiratory irritation. Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. Harmful to aquatic life with long lasting effects.

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS08

Signal word (CLP) :

Danger

Hazardous ingredients :

butanone, ethyl methyl ketone; methylenediphenyl diisocyanate; Hexane, 1,6-diisocyanato-, homopolymer

Hazard statements (CLP) :

H225 - Highly flammable liquid and vapour  
 H315 - Causes skin irritation  
 H317 - May cause an allergic skin reaction  
 H319 - Causes serious eye irritation  
 H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled  
 H335 - May cause respiratory irritation  
 H336 - May cause drowsiness or dizziness  
 H351 - Suspected of causing cancer  
 H412 - Harmful to aquatic life with long lasting effects

Precautionary statements (CLP) :

P102 - Keep out of reach of children  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P280 - Wear eye protection, face protection, protective clothing, protective gloves  
 P284 - [In case of inadequate ventilation] wear respiratory protection  
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower  
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P405 - Store locked up  
 P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

EUH-statements :

EUH204 - Contains isocyanates. May produce an allergic reaction

Child-resistant fastening :

Not applicable

Tactile warning :

Applicable

### 2.3. Other hazards

No additional information available

## SECTION 3: Composition/information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butanone	(CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 (REACH-no) 01-2119457290-43	20 - 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
ethyl methyl ketone	(CAS No) 78-93-3 (EC no) 201-159-0 (EC index no) 606-002-00-3 (REACH-no) 01-2119457290-43	20 - 30	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
n-butyl acetate	(CAS No) 123-86-4 (EC no) 204-658-1 (EC index no) 607-025-00-1 (REACH-no) 01-2119485493-29	5 - 15	Flam. Liq. 3, H226 STOT SE 3, H336
methylenediphenyl diisocyanate (Note C)(Note 2)	(CAS No) 26447-40-5 (EC no) 247-714-0 (EC index no) 615-005-00-9 (REACH-no) 01-2119457015-45	4 - 7	Carc. 2, H351 Acute Tox. 4 (Inhalation), H332 STOT RE 2, H373 Eye Irrit. 2, H319 STOT SE 3, H335 Skin Irrit. 2, H315

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0

			Resp. Sens. 1, H334 Skin Sens. 1, H317
Hexane, 1,6-diisocyanato-, homopolymer	(CAS No) 28182-81-2 (REACH-no) 01-2119485796-17	2 - 5	Acute Tox. 4 (Inhalation), H332 Skin Sens. 1, H317 STOT SE 3, H335
Silane, trimethoxy[3-(oxiranylmethoxy)propyl]-	(CAS No) 2530-83-8 (REACH-no) 01-211937949916	< 2.5	Eye Dam. 1, H318
2-methoxy-1-methylethyl acetate	(CAS No) 108-65-6 (EC no) 203-603-9 (EC index no) 607-195-00-7 (REACH-no) 01-2119475791-29	< 2	Flam. Liq. 3, H226
dibutyltin dichloride, (DBTC) substance listed as REACH Candidate (Dibutyltin dichloride (DBTC))	(CAS No) 683-18-1 (EC no) 211-670-0 (EC index no) 050-022-00-X (REACH-no) 01-2119496066-31	< 0.1	Muta. 2, H341 Repr. 1B, H360FD Acute Tox. 2 (Inhalation), H330 Acute Tox. 3 (Oral), H301 Acute Tox. 4 (Dermal), H312 STOT RE 1, H372 Skin Corr. 1B, H314 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

### Specific concentration limits:

Name	Product identifier	Specific concentration limits
methylenediphenyl diisocyanate	(CAS No) 26447-40-5 (EC no) 247-714-0 (EC index no) 615-005-00-9 (REACH-no) 01-2119457015-45	(C >= 0.1) Resp. Sens. 1, H334 (C >= 5) STOT SE 3, H335 (C >= 5) Skin Irrit. 2, H315 (C >= 5) Eye Irrit. 2, H319
dibutyltin dichloride, (DBTC)	(CAS No) 683-18-1 (EC no) 211-670-0 (EC index no) 050-022-00-X (REACH-no) 01-2119496066-31	( 0.01 =<C < 5) Skin Irrit. 2, H315 ( 0.01 =<C < 3) Eye Irrit. 2, H319 ( 3 =<C < 5) Eye Dam. 1, H318 (C >= 5) Skin Corr. 1B, H314

Note 2 : The concentration of isocyanate stated is the percentage by weight of the free monomer calculated with reference to the total weight of the mixture.

Note C : Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.

Full text of H-statements: see section 16

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures general	: IF exposed or concerned: Get medical advice/attention. Call a poison center or a doctor if you feel unwell.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing. Call a poison center or a doctor if you feel unwell.
First-aid measures after skin contact	: Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries	: May cause drowsiness or dizziness.
Symptoms/injuries after inhalation	: May cause respiratory irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Symptoms/injuries after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/injuries after eye contact	: Eye irritation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

### 5.2. Special hazards arising from the substance or mixture

Fire hazard	: Highly flammable liquid and vapour.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

### 5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. For non-emergency personnel

Emergency procedures : Ventilate spillage area. No open flames, no sparks, and no smoking. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

#### 6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

### 6.2. Environmental precautions

Avoid release to the environment.

### 6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

### 6.4. Reference to other sections

For further information refer to section 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapours may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with skin and eyes.

Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

### 7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

### 7.3. Specific end use(s)

No additional information available

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

TECH-FLEX Black Primer 1L		
EU	Local name	Butanone
EU	IOELV TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
EU	IOELV TWA (ppm)	200 ppm
EU	IOELV STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
EU	IOELV STEL (ppm)	300 ppm
Austria	Local name	Butanon
Austria	MAK (mg/m <sup>3</sup> )	295 mg/m <sup>3</sup>
Austria	MAK (ppm)	100 ppm
Austria	MAK Short time value (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
Austria	MAK Short time value (ppm)	200 ppm
Austria	Remark (AT)	H
Belgium	Local name	2-Butanone
Belgium	Limit value (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Belgium	Limit value (ppm)	200 ppm
Belgium	Short time value (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Belgium	Short time value (ppm)	300 ppm
Bulgaria	Local name	Метилетилкетон (бутанон)•
Bulgaria	OEL TWA (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

Bulgaria	OEL STEL (mg/m <sup>3</sup> )	885 mg/m <sup>3</sup>
Croatia	Local name	Butanon (metil-etil-ke-ton)
Croatia	GVI (granična vrijednost izloženosti) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Croatia	GVI (granična vrijednost izloženosti) (ppm)	200 ppm
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Croatia	KGVI (kratkotrajna granična vrijednost izloženosti) (ppm)	300 ppm
Croatia	Naznake (HR)	K, F, Xi EU*
Czech Republic	Local name	2-Butanon
Czech Republic	Expoziční limity (PEL) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (PEL) (ppm)	203 ppm
Czech Republic	Expoziční limity (NPK-P) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Czech Republic	Expoziční limity (NPK-P) (ppm)	305 ppm
Czech Republic	Remark (CZ)	S
Denmark	Local name	Butanon (1994)
Denmark	Grænseværdie (langvarig) (mg/m <sup>3</sup> )	145 mg/m <sup>3</sup>
Denmark	Grænseværdie (langvarig) (ppm)	50 ppm
Denmark	Anmærkninger (DK)	EH
Estonia	Local name	2-butanoon
Estonia	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Estonia	OEL TWA (ppm)	200 ppm
Estonia	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Estonia	OEL STEL (ppm)	300 ppm
Finland	Local name	2-Butanoni
Finland	HTP-arvo (15 min)	300 mg/m <sup>3</sup>
Finland	HTP-arvo (15 min) (ppm)	100 ppm
France	Local name	Méthyléthylcétone
France	VME (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
France	VME (ppm)	200 ppm
France	VLE (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
France	VLE (ppm)	300 ppm
Germany	Local name	Butanon
Germany	TRGS 900 Occupational exposure limit value (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Germany	TRGS 900 Occupational exposure limit value (ppm)	200 ppm
Germany	Remark (TRGS 900)	DFG,EU,H,Y
Greece	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Greece	OEL TWA (ppm)	200 ppm
Greece	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Greece	OEL STEL (ppm)	300 ppm
Hungary	Local name	METIL-ETIL-KETON
Hungary	AK-érték	600 mg/m <sup>3</sup>
Hungary	CK-érték	900 mg/m <sup>3</sup>
Hungary	Megjegyzések (HU)	b, i; II.1.
Ireland	Local name	Methyl ethyl ketone (MEK)
Ireland	OEL (8 hours ref) (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Ireland	OEL (15 min ref) (ppm)	300 ppm
Ireland	Notes (IE)	Sk, IOELV
Italy	Local name	Butanone
Italy	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Italy	OEL TWA (ppm)	200 ppm
Italy	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Italy	OEL STEL (ppm)	300 ppm
Latvia	Local name	2-Butanons (metiltilketons, etilmetilketons)

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

Latvia	OEL TWA (mg/m <sup>3</sup> )	200 mg/m <sup>3</sup>
Latvia	OEL TWA (ppm)	67 ppm
Latvia	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Latvia	OEL STEL (ppm)	300 ppm
Lithuania	Local name	Butanonas (metiletilketonas)
Lithuania	IPRV (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Lithuania	IPRV (ppm)	200 ppm
Lithuania	TPRV (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Lithuania	TPRV (ppm)	300 ppm
Lithuania	NRV (mg/m <sup>3</sup> )	0.1 mg/m <sup>3</sup>
Lithuania	NRV (ppm)	0.01 ppm
Lithuania	Remark (LT)	J
Luxembourg	Local name	Butanone
Luxembourg	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Luxembourg	OEL TWA (ppm)	200 ppm
Luxembourg	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Luxembourg	OEL STEL (ppm)	300 ppm
Malta	Local name	Butanone
Malta	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Malta	OEL TWA (ppm)	200 ppm
Malta	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Malta	OEL STEL (ppm)	300 ppm
Netherlands	Local name	2-Butanon
Netherlands	Grenswaarde TGG 8H (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
Netherlands	Grenswaarde TGG 15MIN (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Netherlands	Remark (MAC)	H
Poland	Local name	Butan-2-on
Poland	NDS (mg/m <sup>3</sup> )	450 mg/m <sup>3</sup>
Poland	NDSch (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Portugal	Local name	Metiletilcetona (MEK) (2-Butanona)
Portugal	OEL TWA (ppm)	200 ppm
Portugal	OEL STEL (ppm)	300 ppm
Slovenia	Local name	butanol (etilmetilketon)
Slovenia	OEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Slovenia	OEL TWA (ppm)	200 ppm
Slovenia	OEL STEL (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Slovenia	OEL STEL (ppm)	300 ppm
Spain	Local name	Metiletilcetona (Butanona)
Spain	VLA-ED (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
Spain	VLA-ED (ppm)	200 ppm
Spain	VLA-EC (mg/m <sup>3</sup> )	900 mg/m <sup>3</sup>
Spain	VLA-EC (ppm)	300 ppm
Spain	Notes	VLB® (Agente químico que tiene Valor Límite Biológico específico en este documento.), VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país.)
Sweden	Local name	Methyl ethyl ketone
Sweden	nivågränsvärde (NVG) (mg/m <sup>3</sup> )	150 mg/m <sup>3</sup>
Sweden	nivågränsvärde (NVG) (ppm)	50 ppm
Sweden	kortidsvärde (KTV) (mg/m <sup>3</sup> )	300 mg/m <sup>3</sup>
Sweden	kortidsvärde (KTV) (ppm)	100 ppm
Sweden	takgränsvärde (TGV) (mg/m <sup>3</sup> )	0.05 mg/m <sup>3</sup>

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0

Sweden	takgränsvärde (TGV) (ppm)	0.005 ppm
United Kingdom	Local name	Butan-2-one (methyl ethyl ketone)
United Kingdom	WEL TWA (mg/m <sup>3</sup> )	600 mg/m <sup>3</sup>
United Kingdom	WEL TWA (ppm)	200 ppm
United Kingdom	WEL STEL (mg/m <sup>3</sup> )	899 mg/m <sup>3</sup>
United Kingdom	WEL STEL (ppm)	300 ppm
United Kingdom	Remark (WEL)	Sk (Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity), BMGV (Biological monitoring guidance values are listed in Table 2)
Norway	Local name	Butanon
Norway	Grenseverdier (AN) (mg/m <sup>3</sup> )	220 mg/m <sup>3</sup>
Norway	Grenseverdier (AN) (ppm)	75 ppm
Norway	Merknader (NO)	A
Switzerland	Local name	2-Butanone
Switzerland	VME (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
Switzerland	VME (ppm)	200 ppm
Switzerland	VLE (mg/m <sup>3</sup> )	590 mg/m <sup>3</sup>
Switzerland	VLE (ppm)	200 ppm
Switzerland	Remark (CH)	15 min
Australia	Local name	Methyl ethyl ketone (MEK)
Australia	TWA (mg/m <sup>3</sup> )	445 mg/m <sup>3</sup>
Australia	TWA (ppm)	150 ppm
Australia	STEL (mg/m <sup>3</sup> )	890 mg/m <sup>3</sup>
Australia	STEL (ppm)	300 ppm
USA - ACGIH	Local name	Methyl ethyl ketone (MEK)
USA - ACGIH	ACGIH TWA (ppm)	200 ppm
USA - ACGIH	ACGIH STEL (ppm)	300 ppm
USA - ACGIH	Remark (ACGIH)	URT irr; CNS & PNS impair

### 8.2. Exposure controls

Appropriate engineering controls	: Ensure good ventilation of the work station.
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Wear suitable protective clothing
Respiratory protection	: Wear respiratory protection
Environmental exposure controls	: Avoid release to the environment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Liquid.
Colour	: Black.
Odour	: characteristic.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butyl acetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 79 °C
Flash point	: -8 °C
Auto-ignition temperature	: >200 °C
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable



# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0

Vapour pressure	: No data available
Relative vapour density at 20 °C	: 0.9
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: 20 mPa.s
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: 1.8 vol % 11.5 vol %

### 9.2. Other information

VOC content : < 76 %

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

Highly flammable liquid and vapour.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

### 10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

### 10.5. Incompatible materials

No additional information available

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity	: Not classified
Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Suspected of causing cancer.

Reproductive toxicity	: Not classified
-----------------------	------------------

Specific target organ toxicity (single exposure)	: May cause drowsiness or dizziness. May cause respiratory irritation.
--	--

Specific target organ toxicity (repeated exposure)	: Not classified
--	------------------

Aspiration hazard	: Not classified
-------------------	------------------

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

### 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

No additional information available



# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

### 12.4. Mobility in soil

No additional information available

### 12.5. Results of PBT and vPvB assessment

Component	
dibutyltin dichloride, (DBTC) (683-18-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

### 12.6. Other adverse effects

No additional information available

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.  
Additional information : Flammable vapours may accumulate in the container.

## SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

### 14.1. UN number

UN-No. (ADR) : 1866  
UN-No. (IMDG) : 1866  
UN-No. (IATA) : 1866  
UN-No. (ADN) : 1866  
UN-No. (RID) : 1866

### 14.2. UN proper shipping name

Proper Shipping Name (ADR) : RESIN SOLUTION  
Proper Shipping Name (IMDG) : RESIN SOLUTION  
Proper Shipping Name (IATA) : Resin solution  
Proper Shipping Name (ADN) : RESIN SOLUTION  
Proper Shipping Name (RID) : RESIN SOLUTION  
Transport document description (ADR) : UN 1866 RESIN SOLUTION, 3, II, (D/E)  
Transport document description (IMDG) : UN 1866 RESIN SOLUTION, 3, II  
Transport document description (IATA) : UN 1866 Resin solution, 3, II  
Transport document description (ADN) : UN 1866 RESIN SOLUTION, 3, II  
Transport document description (RID) : UN 1866 RESIN SOLUTION, 3, II

### 14.3. Transport hazard class(es)

#### ADR

Transport hazard class(es) (ADR) : 3  
Danger labels (ADR) : 3



#### IMDG

Transport hazard class(es) (IMDG) : 3  
Danger labels (IMDG) : 3



#### IATA

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0

Transport hazard class(es) (IATA) : 3

Hazard labels (IATA) : 3



### ADN

Transport hazard class(es) (ADN) : 3

Danger labels (ADN) : 3



### RID

Transport hazard class(es) (RID) : 3

Danger labels (RID) : 3



#### 14.4. Packing group

Packing group (ADR) : II

Packing group (IMDG) : II

Packing group (IATA) : II

Packing group (ADN) : II

Packing group (RID) : II

#### 14.5. Environmental hazards

Dangerous for the environment : No

Marine pollutant : No

Other information : No supplementary information available

#### 14.6. Special precautions for user

##### - Overland transport

Classification code (ADR) : F1

Special provisions (ADR) : 640C

Limited quantities (ADR) : 5I

Excepted quantities (ADR) : E2

Packing instructions (ADR) : P001

Special packing provisions (ADR) : PP1

Mixed packing provisions (ADR) : MP19

Portable tank and bulk container instructions (ADR) : T4

Portable tank and bulk container special provisions (ADR) : TP1, TP8

Tank code (ADR) : L1.5BN

Vehicle for tank carriage : FL

Transport category (ADR) : 2

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016

Revision date:

Supersedes:

Version: 2.0

Special provisions for carriage - Operation (ADR) : S2, S20

Hazard identification number (Kemler No.) : 33

Orange plates :



Tunnel restriction code (ADR) : D/E

EAC code : •3YE

### - Transport by sea

Limited quantities (IMDG) : 5 L

Excepted quantities (IMDG) : E2

Packing instructions (IMDG) : P001

Special packing provisions (IMDG) : PP1

IBC packing instructions (IMDG) : IBC02

Tank instructions (IMDG) : T4

Tank special provisions (IMDG) : TP1, TP8

EmS-No. (Fire) : F-E

EmS-No. (Spillage) : S-E

Stowage category (IMDG) : B

Properties and observations (IMDG) : Miscibility with water depends upon the composition.

MFAG-No : 127;128

### - Air transport

PCA Excepted quantities (IATA) : E2

PCA Limited quantities (IATA) : Y341

PCA limited quantity max net quantity (IATA) : 1L

PCA packing instructions (IATA) : 353

PCA max net quantity (IATA) : 5L

CAO packing instructions (IATA) : 364

CAO max net quantity (IATA) : 60L

Special provisions (IATA) : A3

ERG code (IATA) : 3L

### - Inland waterway transport

Classification code (ADN) : F1

Special provisions (ADN) : 640D

Limited quantities (ADN) : 5 L

Excepted quantities (ADN) : E2

Equipment required (ADN) : PP, EX, A

Ventilation (ADN) : VE01

Number of blue cones/lights (ADN) : 1

### - Rail transport

Classification code (RID) : F1

Special provisions (RID) : 640D

Limited quantities (RID) : 5L

Excepted quantities (RID) : E2

Packing instructions (RID) : P001, IBC02, R001

Special packing provisions (RID) : PP1

Mixed packing provisions (RID) : MP19

Portable tank and bulk container instructions (RID) : T4

Portable tank and bulk container special provisions (RID) : TP1, TP8

Tank codes for RID tanks (RID) : LGBF

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0  
 Transport category (RID) : 2  
 Colis express (express parcels) (RID) : CE7  
 Hazard identification number (RID) : 33

### 14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### 15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains a substance on the REACH candidate list in concentration  $\geq 0.1\%$  or with a lower specific limit: Dibutyltin dichloride (DBTC) (EC 211-670-0, CAS 683-18-1)

Contains no REACH Annex XIV substances

VOC content : < 76 %

#### 15.1.2. National regulations

##### Germany

VwVwS Annex reference : Water hazard class (WGK) 1, low hazard to waters (Classification according to VwVwS, Annex 4)

12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV : Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

##### Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed

SZW-lijst van mutagene stoffen : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Borstvoeding : None of the components are listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Vruchtbaarheid : dibutyltin dichloride, (DBTC) is listed

NIET-limitatieve lijst van voor de voortplanting giftige stoffen – Ontwikkeling : dibutyltin dichloride, (DBTC) is listed

##### Denmark

Recommendations Danish Regulation : Young people below the age of 18 years are not allowed to use the product  
 Pregnant/breastfeeding women working with the product must not be in direct contact with the product  
 Persons suffering from asthma or eczema and persons who have chronic lung diseases, skin or respiratory allergies to isocyanates should not work with the material  
 The requirements from the Danish Working Environment Authorities regarding work with epoxy resins and isocyanates must be observed during use and disposal  
 The requirements from the Danish Working Environment Authorities regarding work with carcinogens must be followed during use and disposal

### 15.2. Chemical safety assessment

No chemical safety assessment has been carried out

## SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Carc. 2	Carcinogenicity, Category 2
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2

# TECH-FLEX Black Primer 1L

## Safety Data Sheet

according to Regulation (EU) 2015/830

Date of issue: 4/28/2016      Revision date:      Supersedes:      Version: 2.0

Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Muta. 2	Germ cell mutagenicity, Category 2
Repr. 1B	Reproductive toxicity, Category 1B
Resp. Sens. 1	Sensitisation — Respiratory, Category 1
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, Category 1
STOT RE 1	Specific target organ toxicity — Repeated exposure, Category 1
STOT RE 2	Specific target organ toxicity — Repeated exposure, Category 2
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Respiratory tract irritation
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H301	Toxic if swallowed
H312	Harmful in contact with skin
H314	Causes severe skin burns and eye damage
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H319	Causes serious eye irritation
H330	Fatal if inhaled
H332	Harmful if inhaled
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness
H341	Suspected of causing genetic defects
H351	Suspected of causing cancer
H360FD	May damage fertility. May damage the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H412	Harmful to aquatic life with long lasting effects
EUH204	Contains isocyanates. May produce an allergic reaction

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product*