

Printing date 19.04.2011 Revision: 19.04.2011

# 1 Identification of the substance/mixture and of the company/undertaking

- · Product identifier
- · Trade name: TEKAPUR Polyurethane adhesive for insulation plates
- · Relevant identified uses of the substance or mixture and uses advised against
- · Application of the substance / the preparation

Polyurethane adhesive for fastening insulation materials with the help of a gun for PU foam

- Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

TKK Srpenica ob Soci, d.d.

Srpenica 1

SLO-5224 Srpenica

Further information obtainable from:

Tel: +386 (0) 5 384 13 00 Fax: +386 (0) 5 384 13 90/91

e-mail: tkk@siol.net

· Emergency telephone number: In case of emergeny, consult physician.

2 Hazards ide	ntification		
		stance or mixture egulation (EC) No 1272/2008	
Flam. Aerosol 1	H222	Extremely flammable aerosol.	
GHS08 health h	azard		
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.	
Carc. 2	H351	Suspected of causing cancer.	
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.	
GHS09 environi	ment		
Aquatic Chronic	2 H411	Toxic to aquatic life with long lasting effects.	
GHS07 exclama	ation mark		
Acute Tox. 4	H332	Harmful if inhaled.	
Skin Irrit. 2	H315	Causes skin irritation.	
Eye Irrit. 2	H319	Causes serious eye irritation.	
Skin Sens. 1	H317	May cause an allergic skin reaction.	
STOT SE 3	H335+H336	May cause respiratory irritation. May cause drowsiness or dizziness.	
Lact.	H362	May cause harm to breast-fed children.	
	according to D	irective 67/548/EEC or Directive 1999/45/EC	
Xn; Harmful R20-40-48/20:	Harmful by inhalation. Limited evidence of a carcinogenic effect. Harmful: danger of serious damage to health by prolonged exposure through inhalation.		
Xn; Sensitising			
R42/43:	May cause sensitisation by inhalation and skin contact.		
Xi; Irritant			
R36/37/38:	Irritating to eyes, respiratory system and skin.		
F+; Extremely fl	ammable		
R12:	Extremely flan	nmable.	
R53-64:	May cause lor breastfed bab	ng-term adverse effects in the aquatic environment. May cause harm to ies.	

(Contd. on page 2)

Printing date 19.04.2011 Revision: 19.04.2011

# Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 1)

## · Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

## · Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

## · Label elements

## · Labelling according to EU guidelines:

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

## · Code letter and hazard designation of product:





Xn Harmful F+ Extremely flammable

## · Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

## · Risk phrases:

- 12 Extremely flammable.
- 20 Harmful by inhalation.
- 36/37/38 Irritating to eyes, respiratory system and skin.
- 40 Limited evidence of a carcinogenic effect.
- 42/43 May cause sensitisation by inhalation and skin contact.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 53 May cause long-term adverse effects in the aquatic environment.
- 64 May cause harm to breastfed babies.

## · Safety phrases:

- 2 Keep out of the reach of children.
- 16 Keep away from sources of ignition No smoking.
- 23 Do not breathe aerosol.
- After contact with skin, wash immediately with plenty of soap and water.
- 36/37 Wear suitable protective clothing and gloves.
- 46 If swallowed, seek medical advice immediately and show this container or label.
- 51 Use only in well-ventilated areas.

#### · Special labelling of certain preparations:

Persons already sensitised to diisocyanates may develop allergic reactions when using this product. Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.

This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking. Keep out of the reach of children.

Contains isocyanates. See information supplied by the manufacturer

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C. Do not pierce or burn, even after use.

### Other hazards

- · Results of PBT and vPvB assessment
- · **PBT:** Not applicable.

(Contd. on page 3)

Printing date 19.04.2011 Revision: 19.04.2011

Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 2)

· vPvB: Not applicable.

# 3 Composition/information on ingredients

- \* Chemical characterization: Mixtures
- · **Description**: Mixture of substances listed below with nonhazardous additions.

· Dangerous compo	nents:	
CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues  Xn R20-40-48/20; Xn R42/43; Xi R36/37/38  Carc. Cat. 3  ♦ Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; ♦ Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	40-50%
CAS: 115-10-6 EINECS: 204-065-8	dimethyl ether  ►+ R12  F+ R12  Flam. Gas 1, H220; Press. Gas, H280	
CAS: 13674-84-5	tris(2-chlorisopropyl)-phosphate R52/53 Aquatic Chronic 3, H412	
CAS: 85535-85-9 EINECS: 287-477-0	alkanes, C14-17, chloro N R50/53 R64-66 Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	
CAS: 75-28-5 EINECS: 200-857-2	CAS: 75-28-5 isobutane EINECS: 200-857-2 F+ R12	
CAS: 74-98-6 EINECS: 200-827-9	propane ►+ R12 ◆ Flam. Gas 1, H220; ← Press. Gas, H280	<5%

<sup>·</sup> Additional information: For the wording of the listed risk phrases refer to section 16.

# 4 First aid measures

## Description of first aid measures

General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· After skin contact:

If skin irritation continues, consult a doctor.

Immediately wash with water and soap and rinse thoroughly.

· After eve contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing: Call for a doctor immediately.

GE

Printing date 19.04.2011 Revision: 19.04.2011

Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 3)

# 5 Firefighting measures

# Extinguishing media

· Suitable extinguishing agents:

Foam

CO2, sand, extinguishing powder. Do not use water.

· For safety reasons unsuitable extinguishing agents: Water with full jet

# Special hazards arising from the substance or mixture

In case of fire, the following can be released:

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Hydrogen cyanide (HCN)

- Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## 6 Accidental release measures

# Personal precautions, protective equipment and emergency procedures

Keep away from ignition sources.

Ensure adequate ventilation

Wear protective equipment. Keep unprotected persons away.

## Environmental precautions:

Do not allow to enter sewers/ surface or ground water.

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

### • Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

# Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

# 7 Handling and storage

### · Handling:

### · Precautions for safe handling

Ensure that suitable extractors are available on processing machines

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

## · Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

(Contd. on page 5)

Printing date 19.04.2011 Revision: 19.04.2011

Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 4)

# Conditions for safe storage, including any incompatibilities

· Storage:

## · Requirements to be met by storerooms and receptacles:

Store in a cool location.

Observe official regulations on storing packagings with pressurized containers.

## · Information about storage in one common storage facility:

Store away from oxidizing agents.

Do not store together with acids.

Do not store together with alkalis (caustic solutions).

## · Further information about storage conditions:

Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.

Protect from humidity and water.

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

# 8 Exposure controls/personal protection

- · Additional information about design of technical facilities: No further data; see item 7.
- · Control parameters

## · Ingredients with limit values that require monitoring at the workplace:

## 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues

WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup>

## 115-10-6 dimethyl ether

WEL Short-term value: 958 mg/m<sup>3</sup>, 500 ppm Long-term value: 766 mg/m<sup>3</sup>, 400 ppm

- · Additional information: The lists valid during the making were used as basis.
- Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes and skin.

### Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

## Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several

(Contd. on page 6)

Printing date 19.04.2011 Revision: 19.04.2011

# Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 5)

substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eye protection:



Tightly sealed goggles

# 9 Physical and chemical properties

- Information on basic physical and chemical properties
- · General Information
- · Appearance:

Form: Aerosol

**Colour:** According to product specification

· Odour: Characteristic

· Change in condition

Melting point/Melting range: Undetermined. Boiling point/Boiling range: Undetermined.

• Flash point: Not applicable.

· Ignition temperature: 199 ℃

· **Self-igniting:** Product is not selfigniting.

• **Danger of explosion:** Heating may cause an explosion.

· Explosion limits:

**Lower:** 3.0 Vol % **Upper:** 18.6 Vol %

· **Density:** Not determined.

· Solubility in / Miscibility with

water: Insoluble.

· Solvent content:

**VOC (EC)** 18.5 %

# 10 Stability and reactivity

- · Reactivity
- · Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · Possibility of hazardous reactions No dangerous reactions known.
- · Hazardous decomposition products:

Hydrogen cyanide (prussic acid)

Carbon monoxide

(Contd. on page 7)

Printing date 19.04.2011 Revision: 19.04.2011

Trade name: TEKAPUR Polyurethane adhesive for insulation plates

Nitrogen oxides (NOx)

(Contd. of page 6)

# 11 Toxicological information

- Information on toxicological effects
- · Acute toxicity:
- Primary irritant effect:
- · on the skin: Irritant to skin and mucous membranes.
- · on the eye: Irritating effect.
- · Sensitization:

Sensitization possible through inhalation. Sensitization possible through skin contact.

Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful Irritant

# 12 Ecological information

- · Toxicity
- · Acquatic toxicity: No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.

# 13 Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

# 14 Transport information

Land transport ADR/RID (cross-border)

· ADR/RID class: 2 5F Gases.

· UN-Number: 1950 · Packaging group: -· Hazard label: 2.1

· UN proper shipping name: 1950 AEROSOLS

(Contd. on page 8)

Printing date 19.04.2011 Revision: 19.04.2011

Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 7)

· Remarks: LQ:2

Maritime transport IMDG:
IMDG Class: 2.1
UN Number: 1950
Label 2.1

Packaging group:EMS Number:Marine pollutant:F-D,S-U

· Proper shipping name: AEROSOLS

## · Air transport ICAO-TI and IATA-DGR:

· ICAO/IATA Class: 2.1 · UN/ID Number: 1950 · Label 2.1 · Packaging group: -

· Proper shipping name: AEROSOLS, flammable

- ' UN "Model Regulation": UN1950, AEROSOLS, 2.1
- · Special precautions for user Warning: Gases.

# 15 Regulatory information

· Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

## 16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

## · Relevant phrases

H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335 May cause respiratory irritation. H351 Suspected of causing cancer.

H362 May cause harm to breast-fed children.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.H412 Harmful to aquatic life with long lasting effects.

R12 Extremely flammable. R20 Harmful by inhalation.

R36/37/38 Irritating to eyes, respiratory system and skin. R40 Limited evidence of a carcinogenic effect.

R42/43 May cause sensitisation by inhalation and skin contact.

R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

(Contd. on page 9)

Printing date 19.04.2011 Revision: 19.04.2011

# Trade name: TEKAPUR Polyurethane adhesive for insulation plates

(Contd. of page 8)

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic R50/53

environment.

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic

environment.

R64 May cause harm to breastfed babies.

Repeated exposure may cause skin dryness or cracking. R66

#### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations

Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO) GHS: Globally Harmonized System of Classification and Labelling of Chemicals

VOC: Volatile Organic Compounds (USA, EU)