

## Safety data sheet

according to 1907/2006/EC, Article 31

Printing date 10.11.2017

Revision: 10.11.2017

## SECTION 1: Identification of the substance/mixture and of the company/ undertaking

## <sup>1</sup>1.1 Product identifier

• Trade name: TEKAPUR UNIVERSAL FOAM

<sup>•</sup> 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

· Application of the substance / the mixture One-component polyurethane foam - hand held (B3)

## <sup>1</sup> 1.3 Details of the supplier of the safety data sheet

• Manufacturer/Supplier: TKK d.o.o. Srpenica 1 5224 Srpenica Slovenija

## · Further information obtainable from:

Tel: +386 (0) 5 384 13 00 Fax: +386 (0) 5 384 13 90/91 e-mail: info@tkk.si

\* 1.4 Emergency telephone number: In case of emergency, consult physician

## **SECTION 2: Hazards identification**

## <sup>2</sup>2.1 Classification of the substance or mixture

· Classification according to Regulation (EC) No 1272/2008

	•	0 ( )
Aerosol 1	H222-H229	Extremely flammable aerosol. Pressurised container: May burst if heated.
Acute Tox. 4	H332	Harmful if inhaled.
Skin Irrit. 2	H315	Causes skin irritation.
Eye Irrit. 2	H319	Causes serious eye irritation.
Resp. Sens. 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens. 1	H317	May cause an allergic skin reaction.
Carc. 2	H351	Suspected of causing cancer.
Lact.	H362	May cause harm to breast-fed children.
STOT SE 3	H335	May cause respiratory irritation.
STOT RE 2	H373	May cause damage to organs through prolonged or repeated exposure.

Aquatic Chronic 4 H413 May cause long lasting harmful effects to aquatic life.

## <sup>•</sup> 2.2 Label elements

#### · Labelling according to Regulation (EC) No 1272/2008

- The product is classified and labelled according to the CLP regulation.
- · Hazard pictograms



· Signal word Danger

#### · Hazard-determining components of labelling:

diphenylmethanediisocyanate, isomeres and homologues

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

(Contd. on page 2)

GB

Printing date 10.11.2017

Revision: 10.11.2017

## Trade name: TEKAPUR UNIVERSAL FOAM

	(Contd. of page 1)
H332	Harmful if inhaled.
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H362	May cause harm to breast-fed children.
H335	May cause respiratory irritation.
H373	May cause damage to organs through prolonged or repeated exposure.
H413	May cause long lasting harmful effects to aquatic life.
· Precautio	nary statements
P102	Keep out of reach of children.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition
	sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P260	Do not breathe vapours/spray.
P280	Wear protective gloves/protective clothing/eye protection.
P284	In case of inadequate ventilation wear respiratory protection (a protective mask
	with an appropriate gas filter - i.e. type A1 according to standard EN 14387).
P302+P35	IF ON SKIN: Wash with plenty of water/soap.
P304+P34	0 IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P35	1+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact
	lenses, if present and easy to do. Continue rinsing.
P308+P31	3 IF exposed or concerned: Get medical advice/attention.
P410+P41	2 Protect from sunlight. Do not expose to temperatures exceeding 50 ℃/122 ℃.
P501	Dispose of container to in accordance with local/regional/national/ international
	regulation.
<ul> <li>Additiona</li> </ul>	l information:
Contains is	socyanates. May produce an allergic reaction.

## <sup>•</sup> 2.3 Other hazards

· Results of PBT and vPvB assessment Not applicable.

## **SECTION 3: Composition/information on ingredients**

## <sup>•</sup> 3.2 Chemical characterisation: Mixtures

• **Description:** Mixture of substances listed below with nonhazardous additions.

## · Dangerous components:

CAS: 9016-87-9	diphenylmethanediisocyanate,isomeres and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	25-30%
CAS: 75-28-5 EINECS: 200-857-2	isobutane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	10-15%
	dimethyl ether 🚸 Flam. Gas 1, H220; Press. Gas C, H280	1-10%
	alkanes, C14-17, chloro Aquatic Acute 1, H400; Aquatic Chronic 1, H410; Lact., H362	10-20%
CAS: 74-98-6 EINECS: 200-827-9	propane 🚸 Flam. Gas 1, H220; Press. Gas C, H280	1-10%
• Additional information: For the wording of the listed hazard phrases refer to section 16.		

(Contd. on page 3)

Printing date 10.11.2017

Revision: 10.11.2017

## Trade name: TEKAPUR UNIVERSAL FOAM

(Contd. of page 2)

## **SECTION 4: First aid measures**

#### <sup>•</sup> 4.1 Description of first aid measures

#### General information:

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. • After swallowing: If symptoms persist consult doctor.

- **4.2 Most important symptoms and effects, both acute and delayed** No further relevant information available.
- <sup>•</sup> 4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

## **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents: Foam
- For safety reasons unsuitable extinguishing agents: Water with full jet
- <sup>•</sup> 5.2 Special hazards arising from the substance or mixture

In case of fire, the following can be released: Nitrogen oxides (NOx) Carbon monoxide (CO) Hydrogen cyanide (HCN)

- 5.3 Advice for firefighters
- · Protective equipment: Mouth respiratory protective device.
- Additional information

Cool endangered receptacles with water spray. Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

## SECTION 6: Accidental release measures

- 6.1 Personal precautions, protective equipment and emergency procedures
   Keep away from ignition sources.
   Ensure adequate ventilation
   Wear protective equipment. Keep unprotected persons away.

   6.2 Environmental precautions:
   Inform respective authorities in case of seepage into water course or sewage system.
   Do not allow to enter sewers/ surface or ground water.

   6.3 Methods and material for containment and cleaning up:
   Dispose contaminated material as waste according to item 13.
  - Ensure adequate ventilation.
- **6.4 Reference to other sections** See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

(Contd. on page 4)

GP

Printing date 10.11.2017

Revision: 10.11.2017

## Trade name: TEKAPUR UNIVERSAL FOAM

(Contd. of page 3)

SECTION 7: Handling and storage         7.1 Precautions for safe handling         Ensure that suitable extractors are available on processing machines         Ensure dood ventilation/exhaustion at the workplace.         Open and handle receptacle with care.         Information about fire - and explosion protection:         Keep ignition sources away - Do not smoke.         Protect against electrostatic charges.         7.2 Conditions for safe storage, including any incompatibilities         Storage:         Prequirements to be met by storerooms and receptacles:         Store only in the original receptacle.         Observe official regulations on storing packagings with pressurised containers.         Information about storage in one common storage facility: Store away from oxidising agents.         Further information about storage conditions:         Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.         Protect from humidity and water.         Keep container lightly sealed.         Do not seal receptacle gas light.         Store in cool, dry conditions in well sealed receptacles.         Protect from humidity and water.         7.3 Specific end use(s) No further relevant information available.         Store in cool, dry conditions in well sealed receptacles.         Protect from humidity and water.         7.3 Specific en	
Ensure that suitable extractors are available on processing machines Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. 7.2 Conditions for safe storage, including any incompatibilities Storage: Pequirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle. Deserve official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep continent lighty sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters 9016-87-9 diphenylmethanedlisocyanate, isomeres and homologues WEL [Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as an the end orotantimated clothing	SECTION 7: Handling and storage
Ensure that suitable extractors are available on processing machines Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. 7.2 Conditions for safe storage, including any incompatibilities Storage: Pequirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle. Deserve official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep continent lighty sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters 9016-87-9 diphenylmethanedlisocyanate, isomeres and homologues WEL [Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Long-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as -NCO 115-10-6 dimethyl ether WEL [Short-term value: 0.02 mg/m³ Ser; as an the end orotantimated clothing	· 7 1 Precautions for safe handling
Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges. 7.2 Conditions for safe storage, including any incompatibilities Storage: Requirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle. Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store only in the origin and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. <b>SECTION 8: Exposure controls/personal protection</b> Additional information about design of technical facilities: No further data; see item 7. <b>8.1 Control parameters</b> Negative with limit values that require monitoring at the workplace: <b>9016-87-9 diphenyimethanedilisocyanate.jsomeres and homologues</b> WEL Short-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm Additional information: The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> Personal protective equipment: <b>General protective equipment:</b> <b>General protective equipment:</b> <b>Gene</b>	
<ul> <li>Open and handle receptacle with care.</li> <li>Information about fire - and explosion protection:</li> <li>Keep ignition sources away - Do not smoke.</li> <li>Protect against electrostatic charges.</li> <li>7.2 Conditions for safe storage, including any incompatibilities</li> <li>Storage:</li> <li>Requirements to be met by storerooms and receptacles:</li> <li>Store only in the original receptacle.</li> <li>Observe official regulations on storing packagings with pressurised containers.</li> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool lpace. Heat will increase pressure and may lead to the receptacle bursting.</li> <li>Protect from humidity and water.</li> <li>Keep continer tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>Store in cool, dry conditions in well sealed receptacles.</li> <li>Protect from heat and direct sunlight.</li> <li>7.3 Specific end use(s) No further relevant information available.</li> </ul> SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate, isomeres and homologues WEL Short-term value: 0.02 mg/m <sup>3</sup> Eor; as -NCO 115-10-6 dimethyl ether WEL Cong-term value: 0.02 mg/m <sup>3</sup> Ser; as -NCO 115-10-6 dimethyl ether WEL Additional information: The lists valid during the making were used as basis. A Exposure controls Serios and protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not thale gases (Jumes / aerosols. Avid contact with the eyes and skin.<	
<ul> <li>Information about fire - and explosion protection: Keep ignition sources away - Do not smoke. Protect against electrostatic charges.</li> <li>7.2 Conditions for safe storage, including any incompatibilities</li> <li>Storage: Requirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle. Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from humatiny and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from humatiny conditions in well sealed head humating were used as basis. Protect from thumatiny conditing humating were used as basis. Protect from thumatiny cond</li></ul>	0
<ul> <li>Kepi ginition sources away - Do not smoke.</li> <li>Protect against electrostatic charges.</li> <li><b>7.2 Conditions for safe storage, including any incompatibilities</b></li> <li>Storage:</li> <li>Requirements to be met by storerooms and receptacles:</li> <li>Store only in the original receptacle.</li> <li>Observe official regulations on storing packagings with pressurised containers.</li> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting.</li> <li>Protect from humidity and water.</li> <li>Ree pontainer tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>Store in cool, drive contitions in well sealed receptacles.</li> <li>Protect from heat and direct sunlight.</li> <li><b>7.3 Specific end use(s)</b> No further relevant information available.</li> </ul> <b>SECTION 8: Exposure controls/personal protection</b> <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li><b>8.1 Control parameters</b></li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li><b>9016-87-9 diphenylmethanediisocyanate,isomeres and homologues</b></li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup></li> <li>Sen; as -NCO</li> <li><b>115-10-6 dimethyl ether</b></li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li><b>8.2 Exposure controls</b></li> <li><b>Personal protective equipment:</b></li> <li><b>General protective equipment:</b></li> <li><b>General protective equipment:</b></li> <li><b>General protective equipment:</b></li> <li><b>Metory from solutifs, beverages and feed</b>, Immediately remove all solied and contaminated clothing, Wash hands before breaks and at the end of work.</li> <li><b>Do not indel gases</b> (Times / aerosols.</li> <li><b>Avoid contact with the eyes and s</b></li></ul>	
Protect against electrostatic charges.	
<ul> <li>• 7.2 Conditions for safe storage, including any incompatibilities</li> <li>• Storage:</li> <li>• Requirements to be met by storerooms and receptacles:</li> <li>• Store only in the original receptacle.</li> <li>• Observe official regulations on storing packagings with pressurised containers.</li> <li>• Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>• Further information about storage conditions:</li> <li>• Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.</li> <li>• Keep container tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>• Oro the act and direct sunlight.</li> <li>• 7.3 Specific end use(s) No further relevant information available.</li> </ul> Section 1 (1990) • Additional information about design of technical facilities: No further data; see item 7. • 8.1 Control parameters • Ingredients with limit values that require monitoring at the workplace: • 9016-97-9 diphenylmethanediisocyanate, isomeres and homologues • WEL Short-term value: 0.07 mg/m <sup>3</sup> Sen; as -NCO • 115-10-6 dimethyl ether • WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm • Additional information: The lists valid during the making were used as basis. • 3.2 Exposure controls • Personal protective equipment: • General protective equipment: • Concal protective equipment: • Concal protective equipment: • Concal protective equipment: • Concal protective equipment: • Additional information: The lists valid during the making were used as basis. • Additional information: The lists valid during the making were used as basis. • Additional information: The lists valid during the device. • Additional information: The lists valid during the edd. • Immediately remove all solied and contaminated clothing • Wash hands before breaks and at the end of work.	
<ul> <li>Storage:</li> <li>Requirements to be met by storerooms and receptacles:</li> <li>Store in a cool location.</li> <li>Store only in the original receptacle.</li> <li>Observe official regulations on storing packagings with pressurised containers.</li> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.</li> <li>Keep container tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>Store in cool, dry conditions in well sealed receptacles.</li> <li>Protect from heat and direct sunlight.</li> <li>7.3 Specific end use(s) No further relevant information available.</li> </ul> SECTION 8: Exposure controls/personal protection <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li>8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>9016-87-9 diphenyImethanediisocyanate,isomeres and homologues</li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective end hygienic measures: Keap and from value: 1920 mg/m<sup>3</sup>, 1000 ppm Vaditional information: The lists valid during the making were used as basis. 8.2 Exposure controls Protective and hygienic measures: Keap any from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gase of limes / aerosols. Avoid contact with the eyes and skin. Respiratory protection:<td>Protect against electrostatic charges.</td></li></ul>	Protect against electrostatic charges.
<ul> <li>Storage:</li> <li>Requirements to be met by storerooms and receptacles:</li> <li>Store in a cool location.</li> <li>Store only in the original receptacle.</li> <li>Observe official regulations on storing packagings with pressurised containers.</li> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.</li> <li>Keep container tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>Store in cool, dry conditions in well sealed receptacles.</li> <li>Protect from heat and direct sunlight.</li> <li>7.3 Specific end use(s) No further relevant information available.</li> </ul> SECTION 8: Exposure controls/personal protection <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li>8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>9016-87-9 diphenyImethanediisocyanate,isomeres and homologues</li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Ser; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective end hygienic measures: Kep any from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gase of times / aerosols. Avoid contact with the eyes and skin. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Protection of hands:</li></ul>	7.2 Conditions for safe storage including any incompatibilities
<ul> <li>Requirements to be met by storerooms and receptacles: Store in a cool location. Store only in the original receptacle. Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup>, 1000 ppm 4. Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective equipment: General protective equipment: Metal biods ut for sum and the ord of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. Bespiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. Protection of hands: Personal protection: Nease of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> </ul>	
Store in a cool location. Store only in the original receptacle. Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³. Ser; as -NCO 115-10-6 dimethyl ether WEL Long-term value: 1920 mg/m³, 1000 ppm Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: Mean and before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the yea and skin. Cheginatory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.	
Store only in the original receptacle. Observe official regulations on storing packagings with pressurised containers. Information about storage in one common storage facility: Store away from oxidising agents. Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep container lightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO 115-10-6 dimethyl ether WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the yes and skin. Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.	
<ul> <li>Observe official regulations on storing packagings with pressurised containers.</li> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.</li> <li>Keep container tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>7.3 Specific end use(s) No further relevant information available.</li> </ul> Section 8: Exposure controls/personal protection <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li>8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>9016-87-9 diphenylmethanedlisocyanate,isomeres and homologues</li> <li>WEL Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL [Long-term value: 1920 mg/m³, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienc measures:</li> <li>Keep away from foodstuffs, beverages and feed.</li> <li>Immediately remove all solied and contaminated clothing</li> <li>Wash hands before breaks and at the end of work.</li> <li>Do not inhale gases / fumes / aerosols.</li> <li>Avoid contact with they a and skin.</li> <li>Respiratory protection:</li> <li>In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
<ul> <li>Information about storage in one common storage facility: Store away from oxidising agents.</li> <li>Further information about storage conditions:</li> <li>Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water.</li> <li>Keep container tightly sealed.</li> <li>Do not seal receptacle gas tight.</li> <li>Store in cool, dry conditions in well sealed receptacles.</li> <li>Protect from heat and direct sunlight.</li> <li><b>7.3 Specific end use(s)</b> No further relevant information available.</li> </ul> <b>SECTION 8: Exposure controls/personal protection</b> <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li><b>8.1 Control parameters</b></li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li><b>9016-87-9 diphenylmethanedlisocyanate,Isomeres and homologues</b></li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO</li> </ul> <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm <b>Additional information</b> : The lists valid during the making were used as basis. <b>8.2 Exposure controls Personal protective and hygienic measures:</b> Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. <b>Registratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. <b>Protection of hands: Protection of hands:</b>	Observe official regulations on storing packagings with prossurised containers
<ul> <li>Further information about storage conditions: Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight.</li> <li><b>7.3 Specific end use(s)</b> No further relevant information available.</li> <li><b>SECTION 8: Exposure controls/personal protection</b> <ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li><b>8.1 Control parameters</b> <ul></ul></li></ul></li></ul>	
Store in a cool place. Heat will increase pressure and may lead to the receptacle bursting. Protect from humidity and water. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. <b>7.3 Specific end use(s)</b> No further relevant information available. <b>SECTION 8: Exposure controls/personal protection</b> • Additional information about design of technical facilities: No further data; see item 7. <b>8.1 Control parameters</b> • Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> , 1000 ppm • Additional information: The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> Personal protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. • <b>Respiratory protection</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • <b>Protection of hands:</b>	
Protect from humidity and water. Keep container tightly sealed. Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. <b>7.3 Specific end use(s)</b> No further relevant information available. <b>SECTION 8: Exposure controls/personal protection</b> • Additional information about design of technical facilities: No further data; see item 7. • <b>8.1 Control parameters</b> • Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm • Additional information: The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> Personal protective equipment: • General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solid and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / jumes / aerosols. Avoid contact with the eyes and skin. • <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • <b>Protection of hands:</b>	
Keep container tightly sealed.         Do not seal receptacle gas tight.         Store in cool, dry conditions in well sealed receptacles.         Protect from heat and direct sunlight.         7.3 Specific end use(s) No further relevant information available.         SECTION 8: Exposure controls/personal protection         • Additional information about design of technical facilities: No further data; see item 7.         * A.1 Control parameters         • Ingredients with limit values that require monitoring at the workplace:         9016-87-9 diphenylmethanediisocyanate,isomeres and homologues         WEL         Short-term value: 0.07 mg/m <sup>3</sup> Sen; as -NCO         115-10-6 dimethyl ether         WEL         Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm         • Additional information: The lists valid during the making were used as basis.         • 8.2 Exposure controls         • Personal protective equipment:         • General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all solied and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         • Respiratory protection:         In case of brief exposo	
Do not seal receptacle gas tight. Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. <b>7.3 Specific end use(s)</b> No further relevant information available. <b>SECTION 8: Exposure controls/personal protection</b> <b>4.4 ditional information about design of technical facilities:</b> No further data; see item 7. <b>8.1 Control parameters</b> <b>9.1 Ingredients with limit values that require monitoring at the workplace:</b> <b>9016-87-9 diphenylmethanediisocyanate,isomeres and homologues</b> WEL Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.07 mg/m <sup>3</sup> Sen; as -NCO <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm <b>4.4 ditional information:</b> The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> <b>Personal protective equipment:</b> <b>General protective equipment:</b> <b>General protective equipment:</b> <b>General protective and hygienic measures:</b> Keep away from foodstuffs, beverages and feed. Immediately remove all solled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. <b>7. Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. <b>Protection of hands:</b>	
Store in cool, dry conditions in well sealed receptacles. Protect from heat and direct sunlight. <b>7.3 Specific end use(s)</b> No further relevant information available. <b>SECTION 8: Exposure controls/personal protection</b> • Additional information about design of technical facilities: No further data; see item 7. <b>8.1 Control parameters</b> • Ingredients with limit values that require monitoring at the workplace: <b>9016-87-9 diphenylmethanediisocyanate,isomeres and homologues</b> WEL Short-term value: 0.07 mg/m <sup>3</sup> Long-term value: 0.02 mg/m <sup>3</sup> Ser; as -NCO <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm • Additional information: The lists valid during the making were used as basis. <b>8.2 Exposure controls</b> Personal protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. <b>9. Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • <b>Protection of hands:</b>	
Protect from heat and direct sunlight. 7.3 Specific end use(s) No further relevant information available. SECTION 8: Exposure controls/personal protection Additional information about design of technical facilities: No further data; see item 7. 8.1 Control parameters Ingredients with limit values that require monitoring at the workplace: 9016-87-9 diphenylmethanediisocyanate,isomeres and homologues WEL Short-term value: 0.07 mg/m <sup>3</sup> Sen; as -NCO 115-10-6 dimethyl ether WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm Additional information: The lists valid during the making were used as basis. 8.2 Exposure controls Personal protective equipment: General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. <b>Protection of hands:</b>	
<ul> <li>*7.3 Specific end use(s) No further relevant information available.</li> <li>SECTION 8: Exposure controls/personal protection</li> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li>*8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>9016-87-9 diphenylmethanediisocyanate,isomeres and homologues</li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>*8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all solied and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
SECTION 8: Exposure controls/personal protection         • Additional information about design of technical facilities: No further data; see item 7.         • 8.1 Control parameters         • Ingredients with limit values that require monitoring at the workplace:         9016-87-9 diphenylmethanediisocyanate,isomeres and homologues         WEL       Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO         115-10-6 dimethyl ether         WEL       Long-term value: 1920 mg/m³, 1000 ppm         • Additional information: The lists valid during the making were used as basis.         • 8.2 Exposure controls         • Personal protective equipment:         • General protective end hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         • Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.         • Protection of hands:	
<ul> <li>Additional information about design of technical facilities: No further data; see item 7.</li> <li>8.1 Control parameters</li> <li>Ingredients with limit values that require monitoring at the workplace:</li> <li>9016-87-9 diphenylmethanediisocyanate,isomeres and homologues</li> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective equipment:</li> <li>Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing</li> <li>Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
Ingredients with limit values that require monitoring at the workplace:         9016-87-9 diphenylmethanediisocyanate,isomeres and homologues         WEL       Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO         115-10-6 dimethyl ether         WEL       Long-term value: 1920 mg/m³, 1000 ppm         • Additional information: The lists valid during the making were used as basis.         • 8.2 Exposure controls         • Personal protective equipment:         • General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         • Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.         • Protection of hands:	· Additional information about design of technical facilities: No further data; see item 7.
Ingredients with limit values that require monitoring at the workplace:         9016-87-9 diphenylmethanediisocyanate,isomeres and homologues         WEL       Short-term value: 0.07 mg/m³ Long-term value: 0.02 mg/m³ Sen; as -NCO         115-10-6 dimethyl ether         WEL       Long-term value: 1920 mg/m³, 1000 ppm         • Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.         Protection of hands:	<sup>-</sup> 8.1 Control parameters
<ul> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	Ingredients with limit values that require monitoring at the workplace:
<ul> <li>WEL Short-term value: 0.07 mg/m<sup>3</sup> Long-term value: 0.02 mg/m<sup>3</sup> Sen; as -NCO</li> <li>115-10-6 dimethyl ether</li> <li>WEL Long-term value: 1920 mg/m<sup>3</sup>, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	9016-87-9 diphenvlmethanediisocvanate.isomeres and homologues
Long-term value: 0.02 mg/m <sup>3</sup> Sen; as -NCO <b>115-10-6 dimethyl ether</b> WEL Long-term value: 1920 mg/m <sup>3</sup> , 1000 ppm • Additional information: The lists valid during the making were used as basis. • <b>8.2 Exposure controls</b> • <b>Personal protective equipment:</b> • <b>General protective and hygienic measures:</b> Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. • <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.	
Sen; as -NCO         115-10-6 dimethyl ether         WEL       Long-term value: 1920 mg/m³, 1000 ppm         • Additional information: The lists valid during the making were used as basis.         • 8.2 Exposure controls         • Personal protective equipment:         • General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         • Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.         • Protection of hands:	
115-10-6 dimethyl ether         WEL Long-term value: 1920 mg/m³, 1000 ppm         Additional information: The lists valid during the making were used as basis.         Additional information: The lists valid during the making were used as basis.         8.2 Exposure controls         Personal protective equipment:         General protective and hygienic measures:         Keep away from foodstuffs, beverages and feed.         Immediately remove all soiled and contaminated clothing         Wash hands before breaks and at the end of work.         Do not inhale gases / fumes / aerosols.         Avoid contact with the eyes and skin.         Respiratory protection:         In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.         Protection of hands:	
<ul> <li>WEL Long-term value: 1920 mg/m³, 1000 ppm</li> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	· · ·
<ul> <li>Additional information: The lists valid during the making were used as basis.</li> <li>8.2 Exposure controls</li> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	•
<ul> <li>Second protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
<ul> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	· Additional information: The lists valid during the making were used as basis.
<ul> <li>Personal protective equipment:</li> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	<sup>•</sup> 8.2 Exposure controls
<ul> <li>General protective and hygienic measures: Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
<ul> <li>Keep away from foodstuffs, beverages and feed.</li> <li>Immediately remove all soiled and contaminated clothing</li> <li>Wash hands before breaks and at the end of work.</li> <li>Do not inhale gases / fumes / aerosols.</li> <li>Avoid contact with the eyes and skin.</li> <li>Respiratory protection:</li> <li>In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. • <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • <b>Protection of hands:</b>	
<ul> <li>Wash hands before breaks and at the end of work.</li> <li>Do not inhale gases / fumes / aerosols.</li> <li>Avoid contact with the eyes and skin.</li> <li>Respiratory protection:</li> <li>In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
Do not inhale gases / fumes / aerosols. Avoid contact with the eyes and skin. • <b>Respiratory protection:</b> In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • <b>Protection of hands:</b>	,
<ul> <li>Avoid contact with the eyes and skin.</li> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
<ul> <li>Respiratory protection: In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.</li> <li>Protection of hands:</li> </ul>	
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device. • Protection of hands:	
exposure use self-contained respiratory protective device. Protection of hands:	
· Protection of hands:	
Protective gloves	
Protective gloves	
Protective aloves	
	Protective gloves
(Contd. on page 5) GB	

Printing date 10.11.2017

Revision: 10.11.2017

## Trade name: TEKAPUR UNIVERSAL FOAM

(Contd. of page 4) Protective gloves according to EN 374 The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation **Material of gloves** 

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

• Eye protection:



Tightly sealed goggles

Wear airtight protective goggles EN 166 • Body protection: Protective work clothing EN 13688

## **SECTION 9: Physical and chemical properties**

<sup>•</sup> 9.1 Information on basic physica	l and chemical properties
· General Information	
· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour: · Odour threshold:	Characteristic Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.
· Flash point:	Not applicable, as aerosol.
<ul> <li>Flammability (solid, gas):</li> </ul>	Not applicable.
· Ignition temperature:	199 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Not determined.
· Explosion limits:	
Lower:	3,0 Vol %
Upper:	18,6 Vol %
· Vapour pressure:	Not determined.
· Density:	Not determined.
· Relative density	Not determined.
<ul> <li>Vapour density</li> </ul>	Not determined.
· Evaporation rate	Not applicable.
	(Contd. on page

Printing date 10.11.2017

Revision: 10.11.2017

#### Trade name: TEKAPUR UNIVERSAL FOAM

	(Contd. of page 5)
<ul> <li>Solubility in / Miscibility with water:</li> </ul>	Not miscible or difficult to mix.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity: Dynamic: Kinematic:	Not determined. Not determined.
<ul> <li>Solvent content:</li> <li>VOC (EC)</li> <li>9.2 Other information</li> </ul>	25,7 % No further relevant information available.

## **SECTION 10: Stability and reactivity**

- 10.1 Reactivity No further relevant information available.
- <sup>•</sup> 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- \* 10.3 Possibility of hazardous reactions No dangerous reactions known.
- . 10.4 Conditions to avoid No further relevant information available.
- \* 10.5 Incompatible materials: No further relevant information available.
- <sup>1</sup>10.6 Hazardous decomposition products:

Hydrogen cyanide (prussic acid) Carbon monoxide Nitrogen oxides (NOx)

## **SECTION 11: Toxicological information**

<sup>1</sup>11.1 Information on toxicological effects

• Acute toxicity Harmful if inhaled.

· LD/LC50 values relevant for classification:

## 115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

#### · Primary irritant effect:

- · Skin corrosion/irritation
- Causes skin irritation.
- Serious eye damage/irritation Causes serious eye irritation.

• **Respiratory or skin sensitisation** May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction.

- · CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- Carcinogenicity
- Suspected of causing cancer.
- · Reproductive toxicity
- May cause harm to breast-fed children.
- STOT-single exposure
- May cause respiratory irritation. **STOT-repeated exposure**

May cause damage to organs through prolonged or repeated exposure.

(Contd. on page 7)

GB

Printing date 10.11.2017

Revision: 10.11.2017

## Trade name: TEKAPUR UNIVERSAL FOAM

· Aspiration hazard Based on available data, the classification criteria are not met.

(Contd. of page 6)

## **SECTION 12: Ecological information**

- <sup>·</sup> 12.1 Toxicity
- · Aquatic toxicity: No further relevant information available.
- **12.2 Persistence and degradability** No further relevant information available.
- **12.3 Bioaccumulative potential** No further relevant information available.
- . 12.4 Mobility in soil No further relevant information available.
- · Additional ecological information:
- · General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

• 12.6 Other adverse effects No further relevant information available.

## **SECTION 13: Disposal considerations**

#### <sup>1</sup>13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · European waste catalogue

08 05 01\*waste isocyanates16 05 04\*gases in pressure containers (including halons) containing hazardous substances15 01 10\*packaging containing residues of or contaminated by hazardous substances

· Uncleaned packaging:

• Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number ADR, IMDG, IATA	1950	
14.2 UN proper shipping	name	
· ADR	1950 AEROSOLS	
	AEROSOLS	
	AEROSOLS, flammable	
<sup>•</sup> 14.3 Transport hazard cl	ass(es)	
ADR		
	2 5F Gases.	
	Flammable liquids.	
Label	2.1	
	<b>L</b> . 1	
· IMDG, IATA		
· Class	2.1	
Label	2.1	
14.4 Packing group		
ADR, IMDG, IATA	Void	

Printing date 10.11.2017

Revision: 10.11.2017

#### Trade name: TEKAPUR UNIVERSAL FOAM

	(Contd. of page 7)
<ul> <li>14.5 Environmental hazards:</li> <li>Marine pollutant:</li> </ul>	No
<sup>1</sup> 14.6 Special precautions for us EMS Number:	er Warning: Gases. F-D,S-U
· Transport/Additional information:	
<ul> <li>ADR</li> <li>Limited quantities (LQ)</li> </ul>	11
· UN "Model Regulation":	UN1950, AEROSOLS, 2.1

## **SECTION 15: Regulatory information**

## <sup>•</sup> 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

No further relevant information available.

<sup>15.2</sup> Chemical safety assessment:

A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### · Relevant phrases

H220 Extremely flammable gas. H280 Contains gas under pressure; may explode if heated. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H332 Harmful if inhaled. H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation. H351 Suspected of causing cancer. H362 May cause harm to breast-fed children. H373 May cause damage to organs through prolonged or repeated exposure. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. Abbreviations and acronyms: Flam. Gas 1: Flammable gases - Category 1 Aerosol 1: Aerosols - Category 1 Press. Gas C: Gases under pressure – Compressed gas Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Irrit. 2: Serious eye damage/eye irritation - Category 2 Resp. Sens. 1: Respiratory sensitisation - Category 1 Skin Sens. 1: Skin sensitisation - Category 1 Carc. 2: Carcinogenicity – Category 2 Lact.: Reproductive toxicity - effects on or via lactation STOT SE 3: Specific target organ toxicity (single exposure) - Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) - Category 2 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1 Aquatic Chronic 4: Hazardous to the aquatic environment - long-term aquatic hazard - Category 4